


# High Power RSOA Array Chip on Carrier



## Part Number: COC-179

High Power 4-Channel RSOA Chip on Carrier  
Single-Mode RSOA Array  
CW Wavelength at 1550nm



## Features

- High Output Power
- High Dynamic Range
- High Efficiency
- Standard Low-Cost Package

## Application

- Optical Communications
- LiDAR
- Free Space Communications
- Network Test Equipment




SemiNex delivers the highest available power at infrared wavelengths between 12xx and 19xx nm. When necessary, we will further optimize the design of our InP & GaSb laser chips to meet our customers' specific optical and electrical performance needs. Diodes, bars and packages are tested to meet customer and market performance demands. Typical results and packaging options are shown. Contact SemiNex for additional details or to discuss your specific requirements.

# High Power RSOA Array Chip on Carrier



## Specification

COC-179



Optical	Symbol	Typ.	Units
Center Wavelength	$\lambda_c$	1550	nm
ASE Output Power @1A* per channel	$P_{out}$	0.2	Watts
Aperture Width	AW	4	$\mu m$
Aperture Height	AH	1	$\mu m$
Number of Emitters		4	127 $\mu m$ pitch
3dB Bandwidth	BW	80	nm
Beam Exit Angle	$\theta_{EXT}$	19.5	degree
Polarization Extinction Ratio	PER	18	dB
Fast Axis Div.	$\theta_{\perp}$	30	deg FWHM
Slow Axis Div.	$\theta_{\parallel}$	20	deg FWHM
Front Facet Reflectivity		<0.1%	
Rear Face Reflectivity		98%	
Waveguide		Curved	
Electrical	Symbol		Units
Operating Current per channel	$I_{op}$	1	A
Operating Voltage	$V_{op}$	2	V
Mechanical		Range	Units
Chip Width		625	$\mu m$
Operating Temp.**		-20 to 75	$^{\circ}C$
Storage Temp.		-40 to 85	$^{\circ}C$



\*Specified values are rated at a constant heat sink temperature of 20 $^{\circ}C$ .

\*\*High temperature operation will reduce performance and MTTF.  
Unless otherwise indicated all values are nominal.

# High Power RSOA Array Chip on Carrier



## Mechanical Drawing



All statements, technical information and recommendations related to the product herein are based upon information believed to be reliable or accurate. The accuracy or completeness herein is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. SemiNex Corporation reserves the right to change at any time without notice the design, specification, deduction, fit or form of its described herein, including withdrawal at any time of a product offered for sale herein. Users are encouraged to visit [www.seminex.com](http://www.seminex.com) for the latest data. SemiNex Corporation makes no representations that the products herein are free from any intellectual property claims of others. Please contact SemiNex for more information. 2024 SemiNex Corporation

